



Specifications

Energy Per Blow, Adjustable*

Pump Setting 1	50 %	20.5 / 15,000	kNm / ft-lbs
Pump Setting 2	66 %	26.7 / 19,690	kNm / ft-lbs
Pump Setting 3	83 %	33.6 / 24,760	kNm / ft-lbs
Pump Setting 4	100 %	40.5 / 29,840	kNm / ft-lbs
Frequency		37...52	blows/min
Related Piston Stroke		3.2...1.6 / 10.5...5.3	m / ft.

Maximum batter w/o upper cyl. ext.	1:2	-
with upper cylinder extension	n/a	-
Fuel consumption at full load	4.5 / 1.20	L/hr. / gal./hr.
Oil consumption	0.5 / 0.13	L/hr. / gal./hr.

Approx. Weights

Hammer	2600 / 5,730	kg / lbs.
Piston	1280 / 2,820	kg / lbs.
Hammer with standard guiding	3220 / 7,100	kg / lbs.

Capacities

Fuel Tank	24 / 6.3	L / gal.
Oil Tank	6.5 / 1.7	L / gal.

Dimensions

A	- Length	5580 / 18.3	mm / ft.
LH	- Length, standard	5850 / 19.2	mm / ft.
B	- Center to trip	356 / 14.0	mm / in.
B1	- Center to trip with cylinder	508 / 20.0	mm / in.
C	- Center to pump guard	381 / 15.0	mm / in.
D	- Width of hammer	482 / 19.0	mm / in.
D1	- Width of trip	622 / 24.5	mm / in.
W	- Minimum lead width	534 / 21.0	mm / in.

*September 21, 2006 Technical data are subject to change without prior notice
 Operating energy based on piston stroke – values are approximate.
 Hydraulic start optional.

Pileco, Inc.

P.O. Box 16099 Houston, Texas 77222 USA – Tel. (713) 691-3000 – Facsimile No. (713) 691-0089
 E-mail: pileco@pileco.com – <http://www.pileco.com> Call Toll Free 1-800-231-0421