



## Specifications\*

### Energy Per Blow, Adjustable

Pump Setting 1	64 %	274.8 / 217,600	kNm / ft-lbs
Pump Setting 2	77 %	354.9 / 261,800	kNm / ft-lbs
Pump Setting 3	89 %	410.3 / 302,600	kNm / ft-lbs
Pump Setting 4	100 %	460.9 / 340,000	kNm / ft-lbs
Frequency		36...45	blows/min
Related Piston Stroke		3.4...2.1 / 11.1...7.1	m / ft.

Maximum batter w/o upper cyl. ext.	1:5	-
with upper cylinder extension	1:2	-
Fuel consumption at full load	38.6 / 10.2	L/hr. / gal./hr.
Oil consumption	3.6 / 0.95	L/hr. / gal./hr.

### Approx. Weights


Hammer	26020 / 57,360	kg / lbs.
Piston	13800 / 30,420	kg / lbs.
Hammer with standard guiding	29165 / 64,300	kg / lbs.

### Capacities

Fuel Tank	189 / 50	L / gal.
Oil Tank	60 / 15.8	L / gal.

### Dimensions

<b>A</b>	- Length	7894 / 25.9	mm / ft.
<b>LH</b>	- Length, standard	8475 / 27.8	mm / ft.t.
<b>B</b>	- Center to trip	775 / 30.5	mm / in.
<b>C</b>	- Center to pump guard	572 / 22.5	mm / in.
<b>D</b>	- Width of hammer	1042 / 41.0	mm / in.
<b>D1</b>	- Width of trip	1206 / 47.5	mm / in.
<b>W</b>	- Minimum lead width	1067 / 42	mm / in.



\*September 21, 2006 Technical data are subject to change without prior notice  
 Operating energy based on piston stroke – values are approximate.  
 Hydraulic start optional.

**Pileco, Inc.**

P.O. Box 16099 Houston, Texas 77222 USA – Tel. (713) 691-3000 – Facsimile No. (713) 691-0089  
 E-mail: pileco@pileco.com – <http://www.pileco.com> Call Toll Free 1-800-231-0421