



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	29.2 / 21,510	kNm / ft-lbs
Pump Setting 2	66 %	38.0 / 28,035	kNm / ft-lbs
Pump Setting 3	83 %	47.8 / 35,260	kNm / ft-lbs
Pump Setting 4	100 %	57.6 / 42,480	kNm / ft-lbs
Frequency		37...52	blows/min
Related Piston Stroke		3.2...1.6 / 10.5...5.3	m / ft.

Maximum batter w/o upper cyl. ext.	1:5	-
with upper cylinder extension	1:1	-
Fuel consumption at full load	7.6 / 2.00	L/hr. / gal./hr.
Oil consumption	0.6 / 0.16	L/hr. / gal./hr.

Approx. Weights

Hammer	3795 / 8,365	kg / lbs.
Piston	1820 / 4,015	kg / lbs.
Hammer with standard guiding	4400 / 9,700	kg / lbs.

Capacities

Fuel Tank	75 / 20.0	L / gal.
Oil Tank	19 / 5.0	L / gal.

Dimensions

A	- Length	5610 / 18.4	mm / ft.
LH	- Length, standard	5850 / 19.2	mm / ft.
B	- Center to trip	356 / 14.0	mm / in.
B1	- Center to trip with cylinder	559 / 21.0	mm / in.
C	- Center to pump guard	406 / 16.0	mm / in.
D	- Width of hammer	495 / 19.5	mm / in.
D1	- Width of trip	622 / 24.5	mm / in.
W	- Minimum lead width	534 / 21.0	mm / in.

*September 21, 2006 Technical data are subject to change without prior notice
 Operating energy based on piston stroke – values are approximate.
 Hydraulic start optional.

Pileco, Inc.

P.O. Box 16099 Houston, Texas 77222 USA – Tel. (713) 691-3000 – Facsimile No. (713) 691-0089
 E-mail: pileco@pileco.com – <http://www.pileco.com> Call Toll Free 1-800-231-0421