



## Specifications\*

### Energy Per Blow, Adjustable

Pump Setting 1	64 %	213.8 kNm	157,685 ft.lbs.
Pump Setting 2	77 %	257.9 kNm	190,210 ft.lbs.
Pump Setting 3	89 %	299.7 kNm	221,010 ft.lbs.
Pump Setting 4	100 %	334.1 kNm	246,390 ft.lbs.

Frequency 36 - 45 blows/min

Related Piston Stroke 3.4 - 2.1 m 11.1 - 7.1 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:2 -

Fuel consumption at full load 30.0 L/hr. 7.93 gal./hr.

Oil consumption 2.6 L/hr. 0.68 gal./hr.

### Approx. Weights

Hammer	20364 kg	44,894 lbs.
Piston	10000 kg	22,045 lbs.
Hammer with standard guiding	22135 kg	48,800 lbs.

### Capacities

Fuel Tank	155 L	40.9 gal.
Oil Tank	32 L	8.4 gal.

### Dimensions

A	- Length	7345 mm	24.1 ft.
LH	- Length, standard	8565 mm	28.1 ft.
B	- Center to trip	660 mm	26.0 in.
C	- Center to pump guard	584 mm	23.0 in.
D	- Width of hammer	890 mm	35.0 in.
D1	- Width of trip	1206 mm	47.5 in.
W	- Minimum lead width	1067 mm	42.0 in.

\*Technical data are subject to change without prior notice  
 Operating energy based on piston stroke - values are approximate.  
 Hydraulic start optional.