



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	20.5 kNm	15,000 ft.lbs.
Pump Setting 2	66 %	27.7 kNm	19,690 ft.lbs.
Pump Setting 3	83 %	33.6 kNm	24,760 ft.lbs.
Pump Setting 4	100 %	40.5 kNm	29,840 ft.lbs.

Frequency 37 - 52 blows/min

Related Piston Stroke 3.2 - 1.6 m 10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext. 1:2 -

with upper cylinder extension n/a -

Fuel consumption at full load 4.5 L/hr. 1.20 gal./hr.

Oil consumption 0.5 L/hr. 0.13 gal./hr.

Approx. Weights

Hammer 2600 kg 5,730 lbs.

Piston 1280 kg 2,820 lbs.

Hammer with standard guiding 3220 kg 7,100 lbs.

Capacities

Fuel Tank 24 L 6.3 gal.

Oil Tank 6.5 L 1.7 gal.

Dimensions

A - Length 5580 mm 18.3 ft.

LH - Length, standard 5850 mm 19.2 ft.

B - Center to trip 356 mm 14.0 in.

B1 - Center to trip with cylinder 508 mm 20.0 in.

C - Center to pump guard 381 mm 15.0 in.

D - Width of hammer 482 mm 19.0 in.

D1 - Width of trip 622 mm 24.5 in.

W - Minimum lead width 534 mm 21.0 in.

*Technical data are subject to change without prior notice
 Operating energy based on piston stroke - values are approximate.
 Hydraulic start optional.