



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	64 %	274.8 kNm	217,600 ft.lbs.
Pump Setting 2	77 %	354.9 kNm	261,800 ft.lbs.
Pump Setting 3	89 %	410.3 kNm	302,600 ft.lbs.
Pump Setting 4	100 %	460.9 kNm	340,000 ft.lbs.

Frequency	36 - 45 blows/min	
Related Piston Stroke	3.4 - 2.1 m	11.1 - 7.1 ft.

Maximum batter w/o upper cyl. ext.	1:5	-
with upper cylinder extension	1:2	-
Fuel consumption at full load	38.6 L/hr.	10.2 gal./hr.
Oil consumption	3.6 L/hr.	0.95 gal./hr.

Approx. Weights

Hammer	26020 kg	57,360 lbs.
Piston	13800 kg	30,420 lbs.
Hammer with standard guiding	29165 kg	64,300 lbs.

Capacities

Fuel Tank	189 L	50 gal.
Oil Tank	60 L	15.8 gal.

Dimensions

A	- Length	7894 mm	25.9 ft.
LH	- Length, standard	8475 mm	27.8 ft.
B	- Center to trip	775 mm	30.5 in.
C	- Center to pump guard	572 mm	22.5 in.
D	- Width of hammer	1042 mm	41.0 in.
D1	- Width of trip	1206 mm	47.5 in.
W	- Minimum lead width	1067 mm	42.0 in.

*Technical data are subject to change without prior notice
 Operating energy based on piston stroke - values are approximate.
 Hydraulic start optional.