



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	61 %	368.3 kNm	271,640 ft.lbs.
Pump Setting 2	77 %	463.0 kNm	341,500 ft.lbs.
Pump Setting 3	89 %	535.2 kNm	394,700 ft.lbs.
Pump Setting 4	100 %	601.3 kNm	443,500 ft.lbs.
Frequency	36 - 46 blows/min		
Related Piston Stroke	3.4 - 2.0 m	11.1 - 6.8 ft.	
Maximum batter w/o upper cyl. ext.	1:5	-	
with upper cylinder extension	1:2	-	
Fuel consumption at full load	49.6L/hr.	13.1 gal./hr.	
Oil consumption	5.0 L/hr.	1.32 gal./hr.	

Approx. Weights

Hammer	34340 kg	75,700 lbs.
Piston	18000 kg	39,680 lbs.
Hammer with standard guiding	37470 kg	82,600 lbs.

Capacities

Fuel Tank	238 L	63.0 gal.
Oil Tank	80 L	21.1 gal.

Dimensions

A	- Length	8047 mm	26.4 ft.
LH	- Length, standard	7864 mm	25.8 ft.
B	- Center to trip	856 mm	33.7 in.
C	- Center to pump guard	622 mm	24.7 in.
D	- Width of hammer	1156 mm	45.5 in.
D1	- Width of trip	1300 mm	51.2 in.
W	- Minimum lead width	1220 mm	48.0 in.

*Technical data are subject to change without prior notice
 Operating energy based on piston stroke - values are approximate.
 Hydraulic start optional.