



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	40.0 kNm	29,510 ft.lbs.
Pump Setting 2	74 %	58.5 kNm	38,830 ft.lbs.
Pump Setting 3	90 %	71.1 kNm	52,470 ft.lbs.
Pump Setting 4	100 %	79.0 kNm	58,300 ft.lbs.

Frequency 35 - 50 blows/min

Related Piston Stroke 3.6 - 1.7 m 11.8 - 5.7 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:1 -

Fuel consumption at full load 8.0 L/hr. 2.11 gal./hr.

Oil consumption 1.0 L/hr. 0.26 gal./hr.

Approx. Weights

Hammer	5610 kg	12,370 lbs.
Piston	2500 kg	5,515 lbs.
Hammer with standard guiding	6710 kg	14,800 lbs.

Capacities

Fuel Tank	67 L	17.7 gal.
Oil Tank	19 L	5.0 gal.

Dimensions

A	- Length	5425 mm	17.8 ft.
LH	- Length, standard	6490 mm	21.3 ft.
LH	- Length with hydraulic start	6860 mm	22.5 in.
B	- Center to trip	445 mm	17.5 in.
B1	- Center to trip with cylinder	610 mm	24.0 in.
C	- Center to pump guard	482 mm	19.0 in.
D	- Width of hammer	635 mm	24.5 in.
D1	- Width of trip	812 mm	32.0 in.
W	- Minimum lead width	660 mm	26.0 in.

*Technical data are subject to change without prior notice

Operating energy based on piston stroke - values are approximate.

Hydraulic start and upper cylinder extension optional.