



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	49 %	57.6 kNm	42,500 ft.lbs.
Pump Setting 2	66 %	75.1 kNm	55,410 ft.lbs.
Pump Setting 3	83 %	94.5 kNm	69,680 ft.lbs.
Pump Setting 4	100 %	113.8 kNm	83,950 ft.lbs.

Frequency 37 - 52 blows/min

Related Piston Stroke 3.2 - 1.6 m 10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:1 -

Fuel consumption at full load 11.5 L/hr. 3.04 gal./hr.

Oil consumption 1.5 L/hr. 0.39 gal./hr.

Approx. Weights

Hammer	7880 kg	17,375 lbs.
Piston	3600 kg	7,940 lbs.
Hammer with standard guiding	9026 kg	19,900 lbs.

Capacities

Fuel Tank	89 L	23.5 gal.
Oil Tank	17 L	4.5 gal.

Dimensions

A	- Length	5580 mm	18.3 ft.
LH	- Length, standard	6490 mm	21.3 ft.
LH	- Length with hydraulic start	6860 mm	22.5 in.
B	- Center to trip	482 mm	19.0 in.
B1	- Center to trip with cylinder	660 mm	26.0 in.
C	- Center to pump guard	521 mm	20.5 in.
D	- Width of hammer	724 mm	28.5 in.
D1	- Width of trip	940 mm	37.0 in.
W	- Minimum lead width	812 mm	32.0 in.

*Technical data are subject to change without prior notice

Operating energy based on piston stroke - values are approximate.

Hydraulic start optional.