



## Specifications\*

### Energy Per Blow, Adjustable

Pump Setting 1	50 %	107.4 kNm	79,200 ft.lbs.
Pump Setting 2	66 %	145.7 kNm	107,490 ft.lbs.
Pump Setting 3	83 %	181.9 kNm	134,160 ft.lbs.
Pump Setting 4	100 %	219.2 kNm	161,640 ft.lbs.
Frequency	35 - 50 blows/min		
Related Piston Stroke	3.6 - 1.7 m	11.8 - 5.7 ft.	
Maximum batter w/o upper cyl. ext.	1:5	-	
with upper cylinder extension	1:1	-	
Fuel consumption at full load	20.0 L/hr.	5.28 gal./hr.	
Oil consumption	2.0 L/hr.	0.53 gal./hr.	

### Approx. Weights

Hammer	12282 kg	27,077 lbs.
Piston	6200 kg	13,670 lbs.
Hammer with standard guiding	13290 kg	29,300 lbs.

### Capacities

Fuel Tank	98 L	25.8 gal.
Oil Tank	31 L	8.3 gal.

### Dimensions

A	- Length	6890 mm	22.6 ft.
LH	- Length, standard	7560 mm	24.8 ft.
LH	- Length with hydraulic start	7864 mm	25.8 in.
B	- Center to trip	508 mm	20.0 in.
B1	- Center to trip with cylinder	686 mm	27.0 in.
C	- Center to pump guard	648 mm	25.5 in.
D	- Width of hammer	825 mm	32.5 in.
D1	- Width of trip	902 mm	35.5 in.
W	- Minimum lead width	812 mm	32.0 in.

\*Technical data are subject to change without prior notice  
 Operating energy based on piston stroke - values are approximate.  
 Hydraulic start and upper cylinder extension optional.