



## Specifications\*

### Energy Per Blow, Adjustable

Pump Setting 1	64 %	171.1 kNm	126,180 ft.lbs.
Pump Setting 2	74 %	196.7 kNm	145,100 ft.lbs.
Pump Setting 3	89 %	239.8 kNm	176,840 ft.lbs.
Pump Setting 4	100 %	267.3 kNm	197,150 ft.lbs.

Frequency 36 - 45 blows/min

Related Piston Stroke 3.4 - 2.1 m 11.1 - 7.1 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:1 -

Fuel consumption at full load 25.0 L/hr. 6.60 gal./hr.

Oil consumption 2.6 L/hr. 0.68 gal./hr.

### Approx. Weights

Hammer 16907 kg 37,275 lbs.

Piston 8000 kg 17,640 lbs.

Hammer with standard guiding 18690 kg 41,200 lbs.

### Capacities

Fuel Tank 155 L 40.9 gal.

Oil Tank 32 L 8.4 gal.

### Dimensions

A - Length 7195 mm 23.6 ft.

LH - Length, standard 8565 mm 28.1 ft.

B - Center to trip 660 mm 26.0 in.

C - Center to pump guard 584 mm 23.0 in.

D - Width of hammer 890 mm 35.0 in.

D1 - Width of trip 1206 mm 47.5 in.

W - Minimum lead width 1067 mm 42.0 in.

\*Technical data are subject to change without prior notice  
 Operating energy based on piston stroke - values are approximate.  
 Hydraulic start optional.